



CATALOG RACORD T SUDAT SCURT

Racord T sudat scurt Conform EN 10253 Dimensiuni conform ISO/ Metric						
D mm	S mm	Tip	F	h	Kg/buc.	
17.20	1.60	A	25.5	10	0.02	ISO
20.00	2.00	A	25.0	11	0.04	Metric
21.30	2.00	A	25.5	12	0.04	ISO
25.00	2.00	A	29.0	14	0.05	Metric
26.90	2.00	A	28.5	15	0.06	ISO
30.00	2.00	A	38.0	17	0.06	Metric
33.70	2.00	A	38.0	19	0.08	ISO
38.00	2.00	A	47.5	21	0.13	Metric
42.40	2.00	A	47.5	24	0.18	ISO
44.50	2.00	A	47.5	26	0.14	Metric
48.30	2.00	A	57.0	26	0.24	ISO
54.00	2.00	A	57.0	30	0.22	Metric
60.30	2.00	A	63.5	34	0.37	ISO
60.30	3.00	A	63.5	34	0.51	ISO
76.10	2.00	A	76.0	42	0.53	ISO
76.10	3.00	A	76.0	42	0.75	ISO
84.00	2.00	A	85.5	47	0.63	Metric
88.90	2.00	A	85.5	49	0.68	ISO
88.90	3.00	A	85.5	49	0.97	ISO
104.00	2.00	A	105.0	56	0.95	Metric
114.30	2.00	A	105.0	63	1.10	ISO
114.30	3.00	A	105.0	63	1.46	ISO
129.00	2.00	A	124.0	70	1.42	Metric
139.70	2.00	A	124.0	76	1.51	ISO
139.70	3.00	A	124.0	76	2.25	ISO
154.00	2.00	A	143.0	84	2.03	Metric
156.00	3.00	A	143.0	85	3.12	Metric
168.30	2.00	A	142.0	92	2.13	ISO
168.30	3.00	A	142.0	92	3.13	ISO
204.00	2.00	A	178.0	110	3.79	Metric
206.00	3.00	A	178.0	110	4.69	Metric
219.10	2.00	A	179.0	122	3.37	ISO
219.10	3.00	A	179.0	122	4.91	ISO
254.00	2.00	A	250.0	140	5.60	Metric
256.00	3.00	A	250.0	141	8.20	Metric
273.00	2.00	A	216.0	151	5.07	ISO
273.00	3.00	A	216.0	151	7.60	ISO